

MODEL NUMBER:  
**EFP6G**

## Isotropic Broadband Electric Field Probe 100 KHz- 6 GHz, 0.3 - 600 V/m

State of the art probe EFP6G, meets the requirements of new EMC and RF safety standards. It allows measurements of RF fields produced by most of the broadcast, telecommunication and industrial sources. This probe eliminates the need for two probes to cover the required frequency range 100 KHz- 6 GHz, thus making measurements simpler and faster.

### MAIN PARAMETERS\*

Diode based:	3-Axial isotropic sensor
High sensitivity:	0.3 V/m
Linearity:	+/- 0.5 dB (1-400 V/m), +/- 1 dB (400-600 V/m)
Dynamic range:	>66 dB (single range)
Frequency response (without correction factors):	100 KHz-10 MHz (+2.5, -3 dB), 10 MHz-2 GHz (+/- 1 dB), 2-6 GHz (+1, - 4 dB)
Frequency response (with correction factors):	100 KHz-1 GHz (+/1 dB), 1- 6 GHz (+/- 1.5 dB)
Rotational isotropicity:	<1 dB (typical 0.5 dB)
Calibration accuracy (at specified freq.):	<1 dB
Temperature:	5-40 °C
Humidity:	RH 10-90%, non-condensing
Temperature error:	<0.05 dB/°C (field > 2 V/m)
<b>UK NPL or NIST traceable calibration</b>	
Small size (LxD):	9.0x2.25 inch, 230x58 mm
Weight:	0.2 lb, 100 g
Operates with both RFM-04 and RFM-05 meters	
Designed and made in the <b>USA</b>	

\* All system parameters are given for RFM-05 meter.

\* Specification may be changed to reflect the design progress.



**RFM-04**



**RFM-05**

