

MODEL NUMBER:
SS1G-70

SOLID STATE HIGH POWER AMPLIFIER

DESCRIPTION

- Rack mounted system
- Class AB linear LDMOS design
- Instantaneous wide bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

PARAMETER	SPECIFICATION	NOTES
Operating Frequency Range	20 - 1000 MHz	
Power Output	100 Watts (70 Watts P1dB)	Saturated CW
Power Gain	50 dB Min	
Power Gain Flatness	4.0 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	40dBm/Tone, $\Delta = 1$ MHz
Harmonics 2 nd / 3 rd	>25 dBc Typ / 15 dBc Typ	At Rated Pout
Non Harmonics Spurious	60 dBc Min	Non Harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	700 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	$\infty : 1$	

ENVIRONMENTAL CHARACTERISTICS

PARAMETER	SPECIFICATION	NOTES
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

PARAMETER	SPECIFICATION	NOTES
Dimensions W x H x D	430 x 88 x 562 mm	2U
Weight	12 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	AC Power / Interface Connector	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Remote Bluetooth application

OUTLINE DRAWING

