


SHB5H400K

- Magnetic B-Field Sensor Head
- Isotropic
- 1Hz-400kHz
- 80dB dynamic range
- Sensitivity >0.1μT

Features

The SHB5H400K B-field sensor head is based on a set of three mutually orthogonal coils. The three voltages which correspond to the spatial components are individually available at the sensor head output. An SM-series meter (required for use of this sensor head) calculates the resulting isotropic field strength.



The sensor head is supplied with factory calibration. This model is also available in an M1-version which includes an accredited 17025-compliant calibration.

Typical Applications

- Power Lines
- Transformer Stations
- Power Industry
- Magnetic Gates
- Anti-Theft Systems

Specifications

Frequency Range: 1 Hz-400 kHz Type of Frequency Response: Flat Measurement Range: $0.1\mu\text{T}-1 \text{ mT}$

Dynamic Range: >80 dB

Sensor Type: Coils **Directivity:** Isotropic

Accuracy:

Flatness Frequency Response: ± 0.5 dB (50 Hz–50 kHz) @ 30 μ T ± 1 dB (50 kHz–400 kHz) @ 30 μ T

Linearity:

 $\pm 0.5 \text{ dB } (1\mu\text{T}-1 \text{ mT}) @ 50\text{Hz} \\ \pm 0.7 \text{ dB } (500\mu\text{T}-1 \text{ mT}) @ 50\text{Hz}$

Isotropic Response (@ 50 Hz): ±0.5 dB

Operation Temperature: $0^{\circ}C-50^{\circ}C$ Size: 327 x 60 mm, 12.88 x 2.4 in

Weight: 120g, 4.2 oz Export Classification: EAR99

AR RF/Microwave Instrumentation

160 School House Rd Souderton, PA 18964 215-723-8181

For an applications engineer call:800.933.8181

www.arworld.us

To order AR Products, call 215.723.8181. For an applications engineer call:800.933.8181. Direct to Service call: 215.723.0275 or email: service@arworld.us For Faxing Orders:866.859.0582 (Orders Only Please) info@arworld.us Approved for public release by AR RF/Microwave Instrumentation 042718

