

Cable Guide Rail CGR 6.0

Technical Data

Moving range	6.0 m (without clamp)
Total measurement length	6.6 m (with clamp)
Overall length	6.8 m
Track height	0.8 m above floor
Permissible load	15 kg
Material	Plastic + reinforced fibreglass
Cross-section	100 mm x 100 mm
Base L x W	0.3 m x 0.3 m (with supporting pillars)
Positioning speed adjustable between	5.0 – 30.0 cm/s
Positioning accuracy	better +/- 1 cm
Motor	Brushless DC motor 200 W
Interference suppression:	20 dB under limits EN 55022 class B
Current consumption	max. 2A
Voltage	208-230 VAC, 50/60 Hz, single phase
Discharge current	25mA per drive unit (higher in the moment when powering on)
Control cable	Fibre optic lines
Remote control via	IEEE interface
Antenna support drive	Toothed belt
Material of toothed belts	Kevlar reinforced (non-metallic)
Temperature range	+10 °C...+35 °C
Total weight	approx. 75 kg
Accessories	Interface for SCU/MCU/NCD Controller 3 m power supply cable Service manual

Brief description

The **CGR 6.0** cable measuring guide rail, with the exception of the drive unit, is fabricated from plastic (PVC and reinforced fibreglass). Metal parts are located only in the base plate and the drive mechanism (max. 0.3 m above ground level).

The Cable Guide Rail is used for the remotely-controlled positioning of an absorbing clamp along an electric cable. Automatic measurement of the RFI power according to CISPR, EN, ANSI, VCCI and VDE standards are possible.

The **IEEE 488.2 (GPIB) bus** provides an additional control option for all functions, when operated with the **SCU/MCU or NCD Controller**.

Cable Guide Rail CGR 6.0



Information presented enclosed is subject to change as product enhancements are made regularly.
Pictures included are for illustration purposes only and do not represent all possible configurations.